

**SPK 2x4.00 mm<sup>2</sup> speaker (50040)**

High flexible speaker cable for power amplifiers up to 150 watts, 100 volts installations, power mixers, voice and instrument amplifiers may be transmitted safely with this conductor size of 1.0 mm<sup>2</sup>.

Semi-professional connectors are easy to be mounted due to the small overall diameter. Optimal price/quality relation. Small and effective stranding for all application.

same cable available with FRNC Material: 50240



**PVC**

\* Flame retardant PVC, IEC 60332-3

1	Jacket	PVC, ø 9.4 mm, black
2	Insulation	PVC, ø 3.9 mm, black and red
3	Conductor	Stranded bare copper wires, 7x (32 x 0.15 mm) (3.96 mm <sup>2</sup> )

construction

Center conductor resistance	< 4.65 Ohm /km	Test voltage cond/cond	2000 V eff.
Capacitance cond/cond	< 180 nF /km	Temperature range (flex)	- 5° to +50° C
		Temperature range (fix)	-30° to +70° C
Insulation resistance	> 200 MOhm /km	Bending radius min.	5x overall diam.

specifications

Order No.	Type	ø mm	Color	Spool Size	Weight /Spool	Shipping Unit
50040	SPK 2x4.00 mm <sup>2</sup>	9.4	black	100 m	16.5 kg	1 x 100 m

ordering data